

| | |
|------------------|---|
| Model | WA-2L |
| Lamp: | LED Module : 2W - 9W Adjustable |
| Wattage: | 12W Startup draw |
| Input Voltage: | 10.8-13.2VAC/DC (remote transformer required) |
| Kelvin: | 2700K, 3000K, 4000K. CRI = 85 |
| Material: | Machined Aluminum |
| Hardware: | Stainless Steel |
| Finishes: | Seven Polyester Powder Coat |
| Lens: | Tempered Clear Glass |
| Cap Accessories: | Holds two accessories (optional) |
| Mounting: | Three plate options |
| Socket: | GY 6.35 Bi-Pin Porcelain |
| Certification: | Wet location, IP Rating = 66 |
| Wiring: | 10" 18 ga Teflon Coated |
| Weight: | 1.9 lbs. |
| Warranty: | 10 Years |
| Dimensions: | 2 3/8" dia. x 6 1/2" overall |



Shown in Bronze Texture Powder Coat Finish (BZT)



2W/4W/6W/9W



METALS:

6061-T6 Aluminum



Mounting Plate Options:



4/0 Round



4/0 Square



3/0 Round

ORDERING LOGIC:

| | | |
|-----------------|---|--|
| Model: | WA -2L | |
| Metal: | A - Aluminum | |
| Mounting Plate: | 1 - 4/0 Round 3 - 3/0 Round | 2 - 4/0 Square |
| Finish: | BK - Black BZ - Bronze WT - White BG - Beige | BKT - Black Texture BZT - Bronze Texture SL - Silver AC - Aged Copper |

ORDERING EXAMPLE: WA - 2L - A - 1 - BK - 52*

*See page 2 to select module type to be installed

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.



9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-860 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 3 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

| # | Specifications | Lumens |
|----|---------------------|---------|
| 50 | 2W - 9W, 2700K, 15° | 165-720 |
| 51 | 2W - 9W, 2700K, 30° | 165-720 |
| 52 | 2W - 9W, 2700K, 45° | 165-720 |
| 60 | 2W - 9W, 2700K, 60° | 165-720 |
| 53 | 2W - 9W, 3000K, 15° | 190-800 |
| 54 | 2W - 9W, 3000K, 30° | 190-800 |
| 55 | 2W - 9W, 3000K, 45° | 190-800 |
| 61 | 2W - 9W, 3000K, 60° | 190-800 |
| 62 | 2W - 9W, 4000K, 15° | 210-860 |
| 63 | 2W - 9W, 4000K, 30° | 210-860 |
| 64 | 2W - 9W, 4000K, 45° | 210-860 |
| 65 | 2W - 9W, 4000K, 60° | 210-860 |

| Wattage | 2700k | 3000K | 4000K |
|---------|----------|----------|---------|
| 2W | 165 lms | 190 lms | 210 lms |
| 4W | 345 lms. | 360 lms. | 385 lms |
| 6W | 515 lms. | 530 lms. | 590 lms |
| 9W | 720 lms. | 800 lms. | 860 lms |

LENSES INCLUDED

15°



45°



30°



60°

