

MODEL WA-2 12V 50W MR16 8W LED

WA-2

Simply Better by Design™

| Model | WA-2 |
|------------------|------------------------------------|
| Lamp: | MR16 Halogen or LED |
| Maximim Wattage: | 50 watt, 8 watt LED |
| Input Voltage: | 12V (remote transformer required) |
| Material: | Machined Aluminum |
| Hardware: | Stainless Steel |
| Finishes: | Seven Polyester Powder Coat |
| Lens: | Tempered Clear Glass |
| Cap Accessories: | Holds Three accessories (optional) |
| Mounting: | Three plate options |
| Socket: | GY-6.35 Bi Pin Porcelain |
| IP Rating: | 66 |
| Certification: | Wet location |
| Wiring: | 10" 18 ga Teflon Coated |
| Weight: | 1.9 lbs. |
| Warranty: | 10 Years |
| Dimensions: | 2 3/8" dia. x 5 1/2" overall |



METALS:

6061-T6 Aluminum



ORDERING LOGIC:

| Model: | WA - 2 |
|-----------------|--------------------------------|
| Metal: | A - Aluminum |
| Mounting Plate: | 1 - 4/0 Round 3 - 3/0 Round |

2 - 4/0 Square

Finish:

BK - BlackBKTBZ - BronzeBZTWT - WhiteSL -BG - BeigeAC -



ORDERING EXAMPLE: WA - 2 - A - 1 - BK



Shown in Bronze Texture Powder Coat Finish (BZT)



SORAA

DAUER BRILLIANCE

Mounting Plate Options:







4/0 Round

4/0 Square



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

- 1. Machine 6061-T6 copper-free aluminum.
- 2. Anodized pre-treatment applied.
- 3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.