

Model	ST-1
Lamp:	MR16 Halogen or LED
Maximum Wattage:	20 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum or Brass
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat, 2 Brass
Lens:	Tempered Crystalline Spread
Mounting:	Core Drill - 2 3/8" diameter body
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL2108
Wiring:	6' - 16/2 Low Voltage Cable
Weight:	Aluminum: 3.0 lbs.
Warranty:	Aluminum: 10 Years, Brass: 25 Years
Dimensions:	3" x 5" x 3/8" thick faceplate, 6" overall length



Shown in Bronze Powder Coat Finish (BZ)



SORAA DAUER BRILLIANCE



METALS:

6061-T6 Aluminum

Brass



CORE DRILL DESIGN:

Core Drill design for stone, brick or concrete installations. Core size of 2 1/2" is required. Not for use with halogen lamp when mounted in a combustible surface. Six feet of low voltage cable with strain relief is supplied.

ORDERING LOGIC:

Model: ST - 1

Metal: A - Aluminum B - Brass

Finish: BK - Black BKT - Black Texture
 BZ - Bronze BZT - Bronze Texture
 WT - White SL - Silver
 BG - Beige AC - Aged Copper
 NT - Natural DB - Dark Bronze

ORDERING EXAMPLE: ST - 1 - A - BK



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Black anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.

