

Model	IN-5
Lamp:	MR16 Halogen or LED
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Cast Bronze frame & grate; Aluminum Lampholder
Hardware:	Stainless Steel
Finishes:	Natural, Dark Bronze or Powder Coat
Aiming:	18 Degrees
	Hot-Aim Feature available
Lens:	Tempered Clear Glass, Flush lens
Accessories:	Holds Three accessories (optional)
Mounting:	In Ground/Concrete Pour
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	67
Certification:	Wet location
Wiring:	6' 16/2 low voltage cable
Weight:	11.4 lbs.
Warranty:	25 Years
Dimensions:	7 1/2" square x 11 1/4" high



'Hot-Aim' Adjusting Screw

Shown in Black Powder Coat Finish (BK)



SORAA    DAUER    BRILLIANCE



**METALS:**

Cast Bronze



**HOT-AIM FEATURE:**

Our 'hot-aiming' device is an important feature of our Model IN-5 Well Light. This aiming feature allows the lampholder to be adjusted vertically from straight up to 18 degrees from vertical by simply adjusting the socket head screw mounted onto the well light grate. When a project requires many well lights, this feature is an important option you will want to use.

**ORDERING LOGIC:**

Model:	IN - 5	
Metal:	B - Bronze	
Aiming:	S - Standard	H - Hot Aim
Fixture Regress:	1 - 1 3/4" 3 - 4 1/4" (hot-aim)	2 - 3" (standard)
Finish:	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver DB - Dark Bronze AC - Aged Copper



**SELECT-A-FIT:**

Exclusively from Excelsior Lighting, our Xset feature allows you to set your own fixture location within our Models IN4 and IN5 well lights. This feature helps provide the proper fixture location for your lamp beam spread. Spot lamps can be located deeper into the fixture while wide floods can be located closer to the fixture grate. Our simple design offers three grooved locations on the outside of the fixture cap, one inch apart. Simply decide which setting is best for your application and snap the fixture into place!

**ORDERING EXAMPLE:** IN - 5 - B - H - 1 - BK