

Simply Better by Design™

ST-3
MR16 Halogen or LED
20 watt, 8 watt LED
12V (remote transformer required)
Machined Aluminum or Brass
Stainless Steel
Seven Polyester Powder Coat, 2 Brass
Tempered Crystaline Spread
Core Drill - 2 3/8" diameter body
GY-6.35 Bi Pin Porcelain
66
Wet location landscape, UL2108
6' - 16/2 Low Voltage Cable
Aluminum: 3.0 lbs.
Aluminum: 10 Years, Brass: 25 Years
5" x 5" faceplate, 6" overall length



Shown in Bronze Powder Coat Finish (BZ)



SORAA

DAUER BRILLIANCE



METALS:

6061-T6 Aluminum

Brass



ORDERING LOGIC:

Model:	SΤ
--------	----

Metal:	A - A

Finish:

A - Aluminum B - Brass

BK - Black BZ - Bronze WT - White BG - Beige

- 3

ORDERING EXAMPLE: ST - 3 - A - BK

NT - Natural



CORE DRILL DESIGN:

Core Drill design for stone, brick or concrete installations. Core size of 2 1/2" is required. Not for use with halogen lamp when mounted in a combustible surface. Six feet of low voltage cable with strain relief is supplied.



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

- 1. Machine 6061-T6 copper-free aluminum.
- 2. Black anodized pre-treatment applied.
- 3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.