
4W LED



Model	PL-15
Lamp:	T4 Halogen or LED (order separately)
Maximum Wattage:	35 watt, 4 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Aluminum or Brass - 1 1/4" square
Hardware:	Stainless Steel
Finishes:	Seven Powder Coat, Two Metals*
Lens:	Tempered Frosted Glass
Mounting:	1/2" NPS (order mount separately)
Height:	12" or 20"
Socket:	GY 6.35 Bi-Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	6 ft. 18/2 low voltage cable
Weight:	Brass: 3.8 lbs., Aluminum: 1.8 lbs.
Warranty:	Brass: 25 Years Aluminum: 10 Years
Dimensions:	1 1/4" square tube, 20" H x 7" L









JQ

**BRILLIANCE** 





## **ORDERING LOGIC:**

Model: PL - 15

Metal: A - Aluminum

B - Brass

Height: 12 - 12" 20 - 20"

Finish: BK - Black **BKT - Black Texture** 

> BZT - Bronze Texture BZ - Bronze WT - White SL - Silver

BG - Beige AC - Aged Copper DB - Dark Bronze NT - Natural

ORDERING EXAMPLE: PL - 15 - B - 20- DB



The PL-15 path light is available in aluminum or brass square tubing. The components that house and seal the lamp are machined from copper-free aluminum, then anodized to prevent corrosion from all types of elements. Stainless steel hardware and silicone o-ring seals are standard features. To relamp this luminaire, simply remove one screw and slide out the lamp housing.

Mounting Stake Options:

MT-45 MT-6 MT-8

