

<b>Model</b>	<b>IN-6</b>
<b>Lamp:</b>	MR16 Halogen or LED
<b>Maximim Wattage:</b>	35W halogen, 8W MR16 LED, 18.5W PAR36 LED
<b>Input Voltage:</b>	12V (remote transformer required)
<b>Material:</b>	Cast bronze top & housing
<b>Hardware:</b>	Stainless Steel
<b>Finishes:</b>	Natural, Dark Bronze or Powder Coat
<b>Aiming:</b>	20 degrees (vertical) 360 degrees (rotational) Hot-aim feature is standard (MR16)
<b>Lens:</b>	Tempered Clear Glass lens
<b>Accessories:</b>	Holds up to three accessories (optional) (MR16)
<b>Socket:</b>	GY-6.35 Bi Pin Porcelain (MR16)
<b>IP Rating:</b>	68
<b>Certification:</b>	Wet location
<b>Wiring:</b>	6' 12/2 Low Voltage Cable or 1/2" npsf (2x)
<b>Weight:</b>	8 lbs.
<b>Warranty:</b>	25 Years
<b>Dimensions:</b>	6" dia. x 4" high



Shown in Black Powder Coat Finish (BK)



SORAA



BRILLIANCE



PAR36/AR111



**METALS:**

Cast Bronze



**FLUSH LENS FEATURE:**

To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model IN-6.

**ORDERING LOGIC:**

<b>Model:</b>	IN - 6	
<b>Metal:</b>	B - Cast Bronze	
<b>Lamp:</b>	1 - MR16	2 - PAR36
<b>Accessory:</b>	0 - None	AH - Accessory Holder
<b>Pour Collar:</b>	0 - None	PC - Pour Collar
<b>Wire Entry:</b>	1 - 6 ft 12/2 Cable 2 - Single conduit (1/2" npsf) 3 - Dual conduit (1/2" npsf)	
<b>Finish:</b>	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver DB - Dark Bronze AC - Aged Copper



**ACCESSORY HOLDER:**

The optional accessory holder holds up to three lens/louver accessories. It is a two-piece, machined aluminum part that is threaded so that the lamp and any accessories can be easily installed into the holder. Standard finish is black anodized.



**HOT-AIM FEATURE:**

Our Hot-Aim feature is standard on the IN-6. This aiming feature allows the lampholder to be adjusted vertically from straight up to 18° by simply using the tool supplied. Not available in PAR36 lamping option.

**ORDERING EXAMPLE:** IN - 6 - B - 1 - 0 - PC - 1 - NT