Simply Better by Design™

Model	FD-1
Lamp:	MR11 Halogen (order separately)
Maximum Wattage:	20 watt, 3 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Knuckle:	Tapered & Positive Locking
Lens:	Tempered Clear Glass
Cap Accessories:	Holds Three accessories (optional)
Mounting:	1/2" NPS (order mount separately)
Socket:	GY 6.35 Bi-Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	2ft. 18/2 LV wire leads
Weight:	.7 lbs.
Warranty:	10 Years
Dimensions:	1 3/4" dia. x 5 1/4" overall



3W LED

Shown in Bronze Powder Coat Finish (BZ)







ELI (MR8)

ELI (MR11)

BRILLIANCE







METALS:

6061-T6 Aluminum



Mounting Stake Options:

MT-1 MT-2 MT-6 MT-8 MT-7















Model: FD - 1

Metal: A - Aluminum

Finish: BK - Black BKT - Black Texture

BZT - Bronze Texture BZ - Bronze SL - Silver WT - White

BG - Beige AC - Aged Copper

ORDERING EXAMPLE: FD - 1 - A - BK



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

- 1. Machine 6061-T6 copper-free aluminum.
- 2. Black anodized pre-treatment applied.
- 3. Polyester powder coat finish applied.





SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.