

Simply Better by Design™

| Model | ST-5 |
|------------------|--------------------------------------|
| Lamp: | MR16 Halogen or LED |
| Maximum Wattage: | 20 watt, 8 watt LED |
| Input Voltage: | 12V (remote transformer required) |
| Material: | Machined Aluminum or Brass |
| Hardware: | Stainless Steel |
| Finishes: | Seven Polyester Powder Coat, 2 Brass |
| Lens: | Tempered Linear Spread |
| Mounting: | Core Drill - 2 3/8" diameter body |
| Socket: | GY-6.35 Bi Pin Porcelain |
| IP Rating: | 66 |
| Certification: | Wet location landscape, UL2108 |
| Wiring: | 6' - 16/2 Low Voltage Cable |
| Weight: | Aluminum: 3.0 lbs. |
| Warranty: | Aluminum: 10 Years, Brass: 25 Years |
| Dimensions: | 3" x 5" faceplate, 6" overall length |



Shown in Clear Anodized Aluminum Finish (CA)







SORAA

DAUER

BRILLIANCE



METALS:

6061-T6 Aluminum -



Yellow Brass -




ORDERING LOGIC:

Model: ST - 5

Metal: A - Aluminum B - Brass

Finish: BK - Black **BKT - Black Texture**

> BZ - Bronze BZT - Bronze Texture WT - White SL - Silver



ORDERING EXAMPLE: ST - 5 - B - NT



CORE DRILL DESIGN:

Core Drill design for stone, brick or concrete installations. Core size of 2 1/2" is required. Not for use with halogen lamp when mounted in a combustible surface. Six feet of low voltage cable with strain relief is supplied.



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

- 1. Machine 6061-T6 copper-free aluminum.
- 2. Black anodized pre-treatment applied.
- 3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.

