

Simply Better by Design™

ST- 4
MR16 Halogen or LED
20 watt, 8 watt LED
12V (remote transformer required)
Machined Aluminum or Brass
Stainless Steel
Seven Polyester Powder Coat, 2 Brass
Tempered Crystaline Spread
Core Drill - 2 3/8" diameter body
GY-6.35 Bi Pin Porcelain
66
Wet location landscape, UL2108
6' - 16/2 Low Voltage Cable
Aluminum: 3.0 lbs.
Aluminum: 10 Years, Brass: 25 Years
5 1/2" dia. faceplate, 6" overall length



Shown in Bronze Powder Coat Finish (BZ)



SORAA

DAUER BRILLIANCE







METALS:

6061-T6 Aluminum

Brass



## ORDERING LOGIC:

Metal: Finish: A - Aluminum B - Brass

BK - Black BZ - Bronze WT - White BG - Beige NT - Natural

BZT -	Black Texture Bronze Texture Silver
AC -	Aged Copper
DB -	Dark Brass

## ORDERING EXAMPLE: ST - 4 - A - BK





Core Drill design for stone, brick or concrete installations. Core size of 2 1/2" is required. Not for use with halogen lamp when mounted in a combustible surface. Six feet of low voltage cable with strain relief is supplied.



## ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

- 1. Machine 6061-T6 copper-free aluminum.
- 2. Black anodized pre-treatment applied.
- 3. Polyester powder coat finish applied.



## SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.