

Model	RL-2
Lamp:	MR16 Halogen (order separately)
Maximum Wattage:	50 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Frosted Acrylic Liner/Clear Glass Lens
Mounting:	Brass 1" loop (hook included)
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	12" - 18 ga Shrink Tube Covered, black
Weight:	1.5 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 9" overall



Shown in Bronze Texture Powder Coat Finish (BZT)



SORAA

ELI

BRILLIANCE



METALS:

6061-T6 Aluminum



Optional Frosted Lens at Bottom



Frosted Acrylic Liner is Standard

ORDERING LOGIC:

Model:	RL - 2		
Metal:	A - Aluminum		
Bottom Lens:	0 - None 1 - Frosted lens glued in		
SS Cable:	0 - None 5 - 5 ft 10 - 10 ft	15 - 15 ft 20 - 20 ft 25 - 25 ft	30 - 30 ft
1/2 Wire:	0 - None 5 - 5 ft 10 - 10 ft	15 - 15 ft 20 - 20 ft 25 - 25 ft	30 - 30 ft
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver AC - Aged Copper	



STAINLESS STEEL CABLE:

We offer 1/16" stainless steel cable and hardware for hanging our ring lights. Available in lengths from 5'-30' in five foot increments, we attached one end to the fixture and leave the other end open for the customer to assemble with crimping hardware included. 18/2 low voltage cable is also an option. (see catalog numbering).



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.

ORDERING EXAMPLE: RL - 2 - A - 1 - 0 - 0 - BK