

Specification-grade landscape lighting, wet-location luminaire for step lighting or path lighting applications.

- Available in 2W 160 lumens, 4W 320 lumens.
- · Kelvin options: 2700K, 3000K, 4000K available.
- · Machined aluminum, available in seven standard TGIC powder coat finishes and clear anodized finish.

BOX MOUNT

- · Machined brass available in two finishes.
- · Remote transformer required.
- · Stainless steel hardware.
- · Clear lens.
- · Single gang junction box design.
- · High-temperature silicone O-ring seal used to seal the cap against the body.
- · Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- · Listed for wet location use.
- · Warranty: Aluminum: 10 Years, Brass: 25 Years.









Specifications

MODEL: ST-8L

MATERIAL: Aluminum or Brass

VOLTAGE: 12VDC

WATTAGE: 2 Watt, 4 Watt LAMPING: 1 COB LED (2W/4W) (160 lms./ 320 lms.)



Replaceable LED Module:

Our waterproof LED module is available in 2W and 4W versions. It is field replaceable. Available in three Kelvin choices: 2700K, 3000K and 4000K.

Ordering Logic:

MODEL **METAL WATTAGE KELVIN FINISH**

ST - 8L BK - Black BKT - Black Texture A - Aluminum 2 - 2 Watt 27 - 2700K B - Brass 4 - 4 Watt 30 - 3000K BZ - Bronze BZT - Bronze Texture

> 40 - 4000K WT - White SL - Silver

AC - Aged Copper BG - Beige NT - Natural DB - Dark Brass

ORDERING EXAMPLE: ST - 8L - A - 2 - 27 - BK

Excelsior Lighting, Inc.

PROJECT

TYPE