

Model	PL-25
Lamp:	MR16 Halogen
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Cast/Machined Aluminum
Hardware:	Stainless Steel
Finishes:	7 Polyester Powder Coat
Lens:	Tempered Spread Lens
Mounting:	Wall or Bollard
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	6 ft. 18/2 low voltage cable
Weight:	1.5 lbs./4.5 lbs.
Warranty:	10 Years
Dimensions:	3" W x 3 1/4" L x 5 1/2" H (fixture)



Shown in Bronze Texture Powder Coat Finish (BZT)



SORAA

ELI

BRILLIANCE



METALS:

Cast Aluminum:



Wall Mount



Bollard Mount

BOLLARD MOUNT:

The Model PL-25 Wall Mount fixture is available with an optional Bollard Mount post (2" x 3") in heights of 18", 24" and 36".

Back mounting plate of luminaire is designed to mount onto a single-gang junction box. Mounting base of bollard post has 1/2" NPS threads for attaching to any standard mounting stake or conduit connection.

ORDERING LOGIC:

Model:	PL - 25	
Option:	0 - None	BM - Bollard Mount
Post Height:	0 - none 18 - 18"	24 - 24" 36 - 36"
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver

ORDERING EXAMPLE: PL - 25 - BM - 18 - BZT



Mounting Stake Options:

MT-1

MT-6

