Simply Better by Design™

| Model | PL-7 |
|------------------|-----------------------------------|
| Lamp: | MR16 Halogen or LED |
| Maximum Wattage: | 50 watt, 8 watt LED |
| Input Voltage: | 12V (remote transformer required) |
| Material: | Machined Aluminum |
| Hardware: | Stainless Steel |
| Finishes: | Seven Polyester Powder Coat |
| Lens: | Tempered Clear Glass |
| Cap: | Three cap styles available |
| Mounting: | Adjustable or fixed |
| Stem Length: | 9", 12", 18", 24", 30", 36" |
| Socket: | GY-6.35 Bi Pin Porcelain |
| IP Rating: | 66 |
| Certification: | Wet location |
| Wiring: | 6 ft. 18/2 low voltage cable |
| Weight: | 2.4 lbs. |
| Warranty: | 10 Years |
| Dimensions: | 2 3/8" dia. x 7 1/4" long |



8W LED







SORAA

DAUER

BRILLIANCE



METALS:

6061-T6 Aluminum



ORDERING LOGIC:

Model: PL - 7

Metal: A - Aluminum

Cap: 1 - Flush 2 - Regress

Stem Length:

3 - 45 Degree

9 - 9" 24 - 24" 12 - 12" 30 - 30" 18 - 18" 36 - 36"

Finish: BK - Black **BKT - Black Texture**

BZ - Bronze BZT - Bronze Texture WT - White SL - Silver

BG - Beige AC - Aged Copper

ORDERING EXAMPLE: PL - 7 - A - 1 - 24 - BK

Mounting Stake Options:

MT-45

MT-2 MT-6







MT-8



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

- 1. Machine 6061-T6 copper-free aluminum.
- 2. Anodized pre-treatment applied.
- 3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.