

Model	IN-2
Lamp:	MR16 Halogen (order separately)
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass lens
Accessories:	Holds Three accessories (optional)
Mounting:	In Ground/Concrete Pour
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	67
Certification:	Wet location
Wiring:	6' 16/2 Low Voltage Cable
Weight:	2.5 lbs.
Warranty:	10 Years
Dimensions:	3" dia. x 7" overall (5 1/2" tall housing)



Shown in Bronze Powder Coat Finish (BZ)



SORAA ELI BRILLIANCE



METALS:

6061-T6 Aluminum



FLUSH LENS FEATURE:

To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model IN-2. Caps drain water even when aimed straight up.



ORDERING LOGIC:

Model:	IN - 2	
Metal:	A - Aluminum	
Cutoff Height:	S - Short (1")	T - Tall (1 1/2")
Opening Size:	90 - 90°	180 - 180° (tall only)
Pour Collar:	0 - None (standard) PC - Pour Collar (optional)	
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver AC - Aged Copper

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.



ORDERING EXAMPLE: IN - 2 - A - T - 0 - 90 - BK