

Model	IN-14L
Lamp:	LED Module : 2W - 12W Adjustable
Wattage:	15W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K. CRI = 80
Material:	Cast Bronze or Aluminum frame & grate
Hardware:	Stainless Steel
Finishes:	Natural, Dark Bronze or Powder Coat
Aiming:	10 Degrees
Lens:	Tempered Clear Glass, Flush lens
Accessories:	Holds two accessories (optional)
Mounting:	In Ground/Concrete Pour
Socket:	GY 6.35 Bi-pin Porcelain
Certification:	Wet location, IP Rating = 67
Wiring:	6' 16/2 low voltage cable
Weight:	11.4 lbs.
Warranty:	25 Years (brass only)
Dimensions:	7 1/2 " square x 11 1/4" high



Shown in Natural Bronze Finish (NT)



2W/4W/6W/9W/12W



**METALS:**

Cast Bronze



**AIMING FEATURE:**

Our aiming device is an important feature of our Model IN-4L Well Light. This aiming feature allows the lampholder to be adjusted vertically from up to 10° from vertical by simply adjusting the hinged bracket attached to the well light grate. Remove the lamp housing from the bracket to change the lamp without losing the aiming of the fixture.

**ORDERING LOGIC:**

Model:	IN - 14L	
Metal:	A - Aluminum B - Bronze	
Finish:	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver AC - Aged Copper DB - Dark Bronze

**ORDERING EXAMPLE:** IN - 14L - B - BK - 55\*

\*See Module sheet to select module type to be installed



**SELECT-A-FIT:**

Exclusively from Excelsior Lighting, our Xset feature allows you to set your own fixture location within our Models IN4L and IN5L well lights. This feature helps provide the proper fixture location for your lamp beam spread. Spot lamps can be located deeper into the fixture while wide floods can be located closer to the fixture grate. Our simple design offers three grooved locations on the outside of the fixture cap, one inch apart. Simply decide which setting is best for your application and snap the fixture into place!

12W MULTI-LEVEL - 2W, 4W, 6W, 9W, 12W (210-1165 Lumens)



- True equivalent to MR16 20W/35W/50W Halogen (equivalent CBCP)
- 2700K or 3000K
- Equivalent to either 50W, 35W or 20W halogen light output levels
- 12VAC/DC
- G5.3 bi pin base
- 15W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 3 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field replaceable

#	Specifications	Lumens
50	2W - 12W, 2700K, 15°	210-960
51	2W - 12W, 2700K, 30°	210-960
52	2W - 12W, 2700K, 45°	210-960
60	2W - 12W, 2700K, 60°	210-960
53	2W - 12W, 3000K, 15°	230-1165
54	2W - 12W, 3000K, 30°	230-1165
55	2W - 12W, 3000K, 45°	230-1165
61	2W - 12W, 3000K, 60°	230-1165

Wattage	2700K	3000K
2W	210 lms.	230 lms.
4W	340 lms.	385 lms.
6W	580 lms.	670 lms.
9W	820 lms.	915 lms.
12W	960 lms.	1165 lms.



15° / 30° / 45° / 60°

Beam angle easily changed through replacing lens.

15°



45°



30°



60°

