

Model	SI-1L
Lamp:	LED Module : 2W - 9W Adjustable
Wattage:	12W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K 4000K. CRI = 85
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass, flush lens
Mounting:	4/0 or 3/0 junction covers
Stem Length:	12", 18", 24", 30", 36", 42", 48"
Socket:	GY 6.35 Bi-Pin Porcelain
Certification:	Wet location, IP Rating = 66
Wiring:	2 ft. 16/2 low voltage cable
Weight:	2.4 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 5" (fixture)



Shown in Bronze Powder Coat Finish (BZ)



2W/4W/6W/9W



METALS:

6061-T6 Aluminum



Mounting Options:



4/0 Round



4/0 Square



3/0 Round



4/0 Box

ORDERING LOGIC:

Model: SI - 1L

Metal: A - Aluminum

Mounting Plate: 1 - 4/0 round 2 - 4/0 square
3 - 3/0 round 4 - 4/0 box

Stem Length: 12 - 12" 36 - 36"
18 - 18" 42 - 42"
24 - 24" 48 - 48"
30" - 30"

Finish: BK - Black BKT - Black Texture
BZ - Bronze BZT - Bronze Texture
WT - White SL - Silver
BG - Beige AC - Aged Copper

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



4/0 BOX:

Made for surface mount applications. Fits on to a standard 4/0 junction box. It holds a TR-8 power supply for low voltage fixtures. Accepts standard 4/0 round junction box cover.



ORDERING EXAMPLE: SI - 1L - A - 1 - 24 - BK - 52*

*See page 2 to select module type to be installed

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-860 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 3 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable



#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800
62	2W - 9W, 4000K, 15°	210-860
63	2W - 9W, 4000K, 30°	210-860
64	2W - 9W, 4000K, 45°	210-860
65	2W - 9W, 4000K, 60°	210-860

Wattage	2700k	3000K	4000K
2W	165 lms	190 lms	210 lms
4W	345 lms.	360 lms.	385 lms
6W	515 lms.	530 lms.	590 lms
9W	720 lms.	800 lms.	860 lms

LENSES INCLUDED

15°



45°



30°



60°

