
1" dia.

Specification-grade landscape lighting, wet-location luminaire for down lighting applications. Can be utilized for pergola or tree-mounted installations

- Machined 6061-T6 copper-free aluminum. Aluminum components are black anodized, then a polyester powder coat finish is applied.
- · Seven standard TGIC powder coat finishes and clear anodized finish available.
- · Remote transformer required.
- · SS Cable and lead wire options.
- · Stainless steel hardware.
- 1" brass loop for mounting. Hanging hook included.
- 12" 18 ga. shrink tube covered, black wire leads.
- · Frosted acrylic liner.
- · High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- · Listed for wet location use.
- · Warranty: 10 Years.









Specifications

MODEL: RL-5 LAMPING: MR16 Halogen (order separately)

50W Maximum (order separately)

8W LED (order separately)

MATERIAL: 6061-T6 Aluminum

VOLTAGE: 12V WATTAGE: 50 Watt

SOCKET: GY-6.35 Bi-pin porcelain socket rated 600V,

250°C 18 ga, Teflon® coated leads.

Ordering Logic:

MODEL	METAL	SS CABLE	18/2 WIRE	FINISH	
RL - 5	A - Aluminum	0 - None 5 - 5 ft 10 - 10 ft 15 - 15 ft 20 - 20 ft 25 - 25 ft 30 - 30 ft	0 - None 5 - 5 ft 10 - 10 ft 15 - 15 ft 20 - 20 ft 25 - 25 ft 30 - 30 ft	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver AC - Aged Copper

ORDERING EXAMPLE: RL - 5 - A - 0 - 0 - BK

Excelsior Lighting, Inc.

PROJECT

TYPE