

|                  |                                   |
|------------------|-----------------------------------|
| Model            | DL-7                              |
| Lamp:            | MR11 Halogen (order separately)   |
| Maximum Wattage: | 20 watt, 2 watt LED               |
| Input Voltage:   | 12V (remote transformer required) |
| Material:        | Machined Aluminum                 |
| Hardware:        | Stainless Steel                   |
| Finishes:        | Seven Polyester Powder Coat       |
| Lens:            | Tempered Clear Glass              |
| Cap Accessories: | Holds One accessory (optional)    |
| Mounting:        | 1/2" NPS                          |
| Socket:          | GY 6.35 Bi-Pin Porcelain          |
| IP Rating:       | 66                                |
| Certification:   | Wet location                      |
| Wiring:          | 10" 18 ga Teflon Coated           |
| Weight:          | .4 lbs.                           |
| Warranty:        | 10 Years                          |
| Dimensions:      | 1 5/8" dia. x 3 1/2" overall      |



Shown in Bronze Powder Coat Finish (BZ)



ELI (MR8)



ELI (MR11)



BRILLIANCE



**METALS:**

6061-T6 Aluminum  
Regress Cap




Mounting Plate Options:

4/0 Round



MT-25

3/0 Round



MT-27

Surface



MT-11

Surface



MT-21

**ORDERING LOGIC:**

|                 |   |  |
|-----------------|---|--|
| Model:          | DL - 7  |  |
| Metal:          | A - Aluminum  |  |
| Mounting plate: | 1 - 4/0 Round<br>2 - 3/0 Round                        | 3 - Surface MT-11<br>4 - Surface MT-21   |
| Stem Length:    | 0 - none<br>3 - 3"<br>6 - 6"                          | 9 - 9"<br>12 - 12"<br>18 - 18"   |
| Finish:         | BK - Black<br>BZ - Bronze<br>WT - White<br>BG - Beige | BKT - Black Texture<br>BZT - Bronze Texture<br>SL - Silver<br>AC - Aged Copper |



Various mounting options are available for junction boxes and surface mounting. Stem extensions can be added for the desired application.

**ORDERING EXAMPLE:** DL - 7 - A - 1 - 0 - BK