

| | |
|------------------|---|
| Model | AL-4L |
| Lamp: | LED Module: 2W - 9W Adjustable |
| Wattage: | 12W Startup draw |
| Input Voltage: | 12VAC/DC (remote magnetic transformer required) |
| Kelvin: | 2700K, 3000K, 4000K. CRI = 85 |
| Material: | Machined Aluminum |
| Hardware: | Stainless Steel |
| Finishes: | Seven Polyester Powder Coat |
| Knuckle: | Tapered & Positive Locking |
| Lens: | Tempered Clear Glass, Flush lens |
| Cap Accessories: | Holds two accessories (optional) |
| Mounting: | 1/2" NPS (order mount separately) |
| Socket: | GY 6.35 Bi-Pin Porcelain |
| IP Rating: | 66 |
| Certification: | Wet location |
| Wiring: | 2ft. 18/2 LV wire leads |
| Weight: | 1.6 lbs. |
| Warranty: | 10 Years |
| Dimensions: | 2 3/8" dia. x 7 5/8" length |



Shown in Bronze Powder Coat Finish (BZ)



2W/4W/6W/9W



METALS:

6061-T6 Aluminum



Mounting Stake Options:



FLUSH LENS FEATURE:

To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model AL-4L. Caps drain water even when aimed straight up.

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



ORDERING LOGIC:

| | | |
|---------|--------------|----------------------|
| Model: | AL - 4L | |
| Metal: | A - Aluminum | |
| Finish: | BK - Black | BKT - Black Texture |
| | BZ - Bronze | BZT - Bronze Texture |
| | WT - White | SL - Silver |
| | BG - Beige | AC - Aged Copper |

ORDERING EXAMPLE: AL - 4L - A - BK - 52*

*See Module sheet to select module type to be installed



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees.

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-860 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 3 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

| # | Specifications | Lumens |
|----|---------------------|---------|
| 50 | 2W - 9W, 2700K, 15° | 165-720 |
| 51 | 2W - 9W, 2700K, 30° | 165-720 |
| 52 | 2W - 9W, 2700K, 45° | 165-720 |
| 60 | 2W - 9W, 2700K, 60° | 165-720 |
| 53 | 2W - 9W, 3000K, 15° | 190-800 |
| 54 | 2W - 9W, 3000K, 30° | 190-800 |
| 55 | 2W - 9W, 3000K, 45° | 190-800 |
| 61 | 2W - 9W, 3000K, 60° | 190-800 |
| 62 | 2W - 9W, 4000K, 15° | 210-860 |
| 63 | 2W - 9W, 4000K, 30° | 210-860 |
| 64 | 2W - 9W, 4000K, 45° | 210-860 |
| 65 | 2W - 9W, 4000K, 60° | 210-860 |

| Wattage | 2700k | 3000K | 4000K |
|---------|----------|----------|---------|
| 2W | 165 lms | 190 lms | 210 lms |
| 4W | 345 lms. | 360 lms. | 385 lms |
| 6W | 515 lms. | 530 lms. | 590 lms |
| 9W | 720 lms. | 800 lms. | 860 lms |

LENSES INCLUDED

15°



45°



30°



60°

