

Model	RL-1
Lamp:	MR16 Halogen (order separately)
Maximum Wattage:	50 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass
Cap Accessories:	Holds three accessories (optional)
Mounting:	Brass 1" loop (hook included)
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	12" 18 ga Shrink Tube Covered, black
Weight:	.10 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 4 3/4" (6 1/8") overall



Shown in Bronze Powder Coat Finish (BZ)



Shown in Bronze Texture Finish (BZT)



SORAA



ELI



BRILLIANCE



METALS:

6061-T6 Aluminum



Straight



Angled

ORDERING LOGIC:

Model:	RL - 1		
Metal:	A - Aluminum		
Cap Style:	S - Straight A - 45° Angle		
SS Cable:	0 - None 5 - 5 ft 10 - 10 ft	15 - 15 ft 20 - 20 ft 25 - 25 ft	30 - 30 ft
1/2 Wire:	0 - None 5 - 5 ft 10 - 10 ft	15 - 15 ft 20 - 20 ft 25 - 25 ft	30 - 30 ft
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver AC - Aged Copper	



STAINLESS STEEL CABLE:

We offer 1/16" stainless steel cable and hardware for hanging our ring lights. Available in lengths from 5'-30' in five foot increments, we attached one end to the fixture and leave the other end open for the customer to assemble with crimping hardware included. 18/2 low voltage cable is also an option. (see catalog numbering).



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.

ORDERING EXAMPLE: RL - 1 - A - S - 0 - 0 - BK