

Model	MT-44
Material:	Machined Aluminum
Mount:	Fits onto 4/0 standard J-box
Covers:	3 Cover options
Conduit Connects:	(2) 7/8" slip holes
Finishes:	7 Polyester Powder Coat
Weight:	1.1 lbs.
Warranty:	10 Years
Dimensions:	2" H x 5" diameter



Shown in Bronze Powder Coat Finish (BZ)

**COVERS**



SINGLE



DUAL



SINGLE LOCKING

**METALS:**

6061-T6 Aluminum



**ORDERING LOGIC:**

Model:	MT - 44	
Metal:	A - Aluminum	
Cover:	0 - None 2 - Dual	1 - Single 3 - Single Locking
Style*:	0 - None 2 - 21W (TR - 8)	1 - 60W (TR - 6) 3 - 60W (TR - 9)
Input Voltage:	0 - None 230 - 230 VAC	120 - 120 VAC 277 - 277 VAC
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver AC - Aged Copper

**ORDERING EXAMPLE:** MT - 44 - A - 1 - 1\* - 120 - BK

\*See page 2 for transformer specifications.

## TR-6

- 60W maximum load
- No minimum load
- 12 VDC output
- 120, 230 or 277 VAC input
- 0.625A 50/60Hz
- Designed for LED lamps
- 10 ft. maximum distance per fixture
- Minimum temperature of -15°C and maximum temperature of 90°C
- Dimmable with regular line dimmers
- 2 3/4" L, 1 3/8" W X 1" H
- Damp location use
- 3-year warranty



## TR-8

- 21W maximum load
- No minimum load
- 12 VDC output
- 120-277 VAC input
- 0.22A 63Hz
- Use with ELI 9W or 12W module products
- 10 ft. maximum distance per fixture
- Minimum temperature of -30°C and maximum temperature of 90°C
- Dimmable with regular line dimmers
- 2.76" L, 1.57" W X 1" H
- Damp location use
- 3-year warranty



## TR-9

- 60W maximum load
- 3W minimum load
- 12 VDC output
- 120 VAC input
- 50-60Hz
- Use with ELI 9W, 12W, 17W module products
- 10 ft. maximum distance per fixture
- Minimum temperature of -30°C and maximum temperature of 90°C
- Dimmable with regular line dimmers
- 3.00" L, 1.57" W X 1" H
- Damp location use
- 3-year warranty

