

Model	FD-6
Lamp:	T3 Halogen
Maximum Wattage:	20 watt, 3.5 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Knuckle:	Tapered & Positive Locking
Lens:	Tempered Frosted Glass
Mounting:	1/2" NPS (order mount separately)
Socket:	GY 6.35 Bi-Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	2ft. 18/2 LV wire leads
Weight:	.8 lbs.
Warranty:	10 Years
Dimensions:	1 3/4" dia. x 6" overall



Shown in Bronze Powder Coat Finish (BZ)



JQ



METALS:

6061-T6 Aluminum



Mounting Stake Options:

MT-1 MT-2 MT-6 MT-7 MT-8



DESIGN APPLICATION:

Luminaire can be mounted to a riser stem and used as a down light to light steps, a path or an area.



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Black anodized pre-treatment applied.
3. Polyester powder coat finish applied.

ORDERING LOGIC:

Model:	FD - 6	
Metal:	A - Aluminum	
Finish:	BK - Black	BKT - Black Texture
	BZ - Bronze	BZT - Bronze Texture
	WT - White	SL - Silver
	BG - Beige	AC - Aged Copper

ORDERING EXAMPLE: FD - 6 - A - BK



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into to every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.